1   <u>**Method and Apparatus for Printer Head Error Compensation**</u>

2

3   <u>**Cross Reference**</u>

4   The present application claims the benefit of U.S. Provisional Application

5   No. 60/466,681 filed April 29, 2003.

6

7   <u>**Field of Invention**</u>

8   The present invention relates to a method and apparatus for printer head

9   error compensation.

10

11   <u>**Background of Invention**</u>

12   Referring to Figure 7, a typical printing system includes a data source S

13   such as a computer or scanner, a printer controller C for receiving data

14   from the data source S and a printer head H for printing under control of

15   the printer controller C.   The printer head H is a laser printer head H'

16   shown in Figure 8 or an increasingly popular light-emitting diode ("LED")

17   printer head H" shown in Figures 9~12.

18

19   Referring to Figure 8, the laser printer head H' includes a laser source 62

20   for emitting laser beams, a rotating mirror 64 for reflecting the laser

21   beams, a lens 66 for refracting the laser beams and a drum 68 for taking

22   the laser beams.   Static charges are accumulated on spots on which the

23   laser beams are cast.   The laser printer head H' will not be described in

24   detail for being conventional.

25

26   Referring to Figure 9, the LED printer head H" includes an LED array

1   and driver assembly 70 for producing light beams, an SFL ("self-focusing

2   lens") 72 for focusing the light beams and a photosensitive drum 74 for

3   taking the light beams.   A print image will be formed based on spots of

4   the photosensitive drum 74 that take the LED light beams.

5

6   Referring to Figures 11 and 12, the LED array and driver assembly 70

7   includes a substrate 76, an LED array A installed on the substrate 76 for

8   providing the light beams and a driver D installed on the substrate 76 and

9   connected with the LED array A by means of an interconnection 78.

10   The LED array A is driven by means of the driver D.   The driver D is

11   usually made via a high-density CMOS semiconductor process.

12

13   The LED printer head H" takes up less physical space than the laser

14   printer head H', thus rendering possible a more compact printer.

15   However, the LED printer head H" faces some design challenges.   The

16   most critical is uniformity control of the light-emitting diodes.   It is

17   intended that all of the light-emitting diodes provide brightness at a

18   nominal value.   Because of variation and inaccuracy during fabrication,

19   the light-emitting diodes however differ from one another regarding

20   brightness.   For each LED, the actual brightness can be up to 20% more

21   or less than the nominal value, i.e., the error in brightness can be as much

22   as 20%.   That is, one LED may differ from another in brightness as

23   much as 40% of the nominal value.

24

25   Referring to Figure 12, it has been a standard practice to include built-in

26   compensation logic in the LED printer head H".   To this end, the LED

2

1   printer head H" includes a calibration data memory 80 and a dot on/off

2   controller 82.   The calibration data memory 80 is used for receiving

3   calibration data about the errors in brightness and later sending the

4   calibration data to the driver D.   The calibration data memory is usually

5   implemented as part of the driver chip.   More precisely, there are two

6   memories - a permanent storage such as a flash memory and an EEROM

7   for storing the calibration data and a static or dynamic RAM for storing

8   the calibration data before the calibration data are sent to an exposure

9   control circuit.   With the input of the calibration data for each dot, the

10   driver D can compensate the error in brightness of each LED element via

11   controlling either the electric current intensity or the time duration that

12   each LED element is turned on.   However, it is an expensive practice to

13   include the calibration data memory 80 in the LED printer head H".

14

15   The present invention is therefore intended to obviate or at least alleviate

16   the problems encountered in prior art.

17

18   **Summary of Invention**

19   It is an objective of the present invention to provide an LED printer head

20   with a cost-effective apparatus for error compensation.

21

22   According to the present invention, an LED printing system includes a

23   data source, a printer controller and an LED printer head.   The data

24   source is used to provide original data.   The printer controller is used to

25   provide processed data by means of processing the original data.   The

26   LED printer head is used to print the processed data without further

1   processing them.

2

3   Other objects, advantages and novel features of the invention will become

4   more apparent from the following detailed description in conjunction

5   with the attached drawings.

6

7   **Brief Description of Drawings**

8   The present invention will be described via detailed illustration of

9   embodiments referring to the drawings.

10

11   Figure 1 is a block diagram of a printing system for compensating printer

12   head error according to the present invention.

13

14   Figure 2 is a block diagram of a printing system according to a first

15   embodiment of the present invention.

16

17   Figure 3 is a block diagram of a printing system according to a second

18   embodiment of the present invention.

19

20   Figure 4 is a block diagram of a printing system according to a third

21   embodiment of the present invention.

22

23   Figure 5 is a block diagram of a printing system according to a fourth

24   embodiment of the present invention.

25

26   Figure 6 is a block diagram of a printing system according to a fifth

1   embodiment of the present invention.

2

3   Figure 7 is a block diagram of a printing system according to prior art.

4

5   Figure 8 is a simplified perspective view of a laser printer head.

6

7   Figure 9 is a simplified perspective view of an LED printer head.

8

9   Figure 10 is a side view of the LED printer head of Figure 9.

10

11 Figure 11 is a simplified perspective view of an LED array and driver

12 assembly for use in the LED printer of Figure 9.

13

14 Figure 12 is a block diagram of the LED printer head of Figure 9.

15

16   **Detailed Description of Embodiments**

17 Figure 1 shows a printing system 10 in which a method for printer head

18 error compensation according to the present invention is performed.

19 The printing system 10 includes a data source S such as a computer or

20 scanner, a printer controller C for receiving data from the data source S

21 and an LED printer head H for printing under control of the printer

22 controller C.

23

24 The LED printer head H includes a dot controller 11 for receiving the

25 processed data from the printer controller C and an LED array 13 for

26 printing under control of the dot controller 11.   In a one-bit-per-pixel

1 printing system, the dot controller 11 controls the on/off of each dot

2 related to every LED of the LED array 13.   In a multi-bit-per-pixel

3 printing system, the dot controller 11 controls not only the on/off of every

4 dot but also the size of every dot that is turned on via current or exposure

5 time control.   Not like any conventional LED printer head, the LED

6 printer head H does not include a memory for storing calibration data.

7

8 Figure 2 shows a printing system according to a first embodiment of the

9 present invention.   The printer controller C includes a dither block 12, a

10 multiplier 14 connected with the dither block 12 and a calibration data

11 memory 30 connected with the multiplier 14.   Calibration data of the

12 LED printer head H are stored in the calibration data memory 30.   In the

13 multiplier 14, multiplication is performed.   In the dither block 12, a

14 dither algorithm is performed.   The calibration data memory 30 and the

15 dither block 12 will not be described in detail for being conventional.

16

17 In operation, source data are provided to the multiplier 14 from the data

18 source S.   The calibration data are sent to the multiplier 14 from the

19 calibration data memory 30.   In the multiplier 14, the source datum of

20 each dot is multiplied by the calibration datum of said dot.   The

21 multiplied data are sent to dither block 12 from the multiplier 14.   In the

22 dither block 12, the multiplier data are dithered.   The dithered data are

23 sent to the LED printer head H from the dither block 12.

24

25 Figure 3 shows a printing system according to a second embodiment of

26 the present invention conducting a dither algorithm based on a threshold

1   array.   The printer controller C includes a dither block 12, a multiplier

2   14 connected with the dither block 12, a calibration data memory 30

3   connected with the multiplier 14 and a threshold memory 40 connected

4   with the multiplier 14.   The printer controller C of the second

5   embodiment is identical to the printer controller C of the first

6   embodiment except for including the threshold memory 40 for storing the

7   threshold array.   The threshold memory 40 will not be described in detail

8   for being conventional.

9

10 In operation, the source data are sent to the dither block 12 from the data

11 source S.   The calibration data are sent to the multiplier 14 from the

12 calibration data memory 30.   The threshold array is sent to the multiplier

13 14 from the threshold memory 40.   In the multiplier 14, all of the

14 thresholds in the threshold array are multiplied by the calibration data, i.e.,

15 the threshold array is modified.   In the dither block 12, the source data

16 are compared with the modified threshold array and dithered.   The

17 dithered data are sent to the LED printer head H from the dither block 12.

18

19 As discussed above, the error in brightness of each LED of the LED

20 printer head H is compensated by means of the method and apparatus

21 according to the present invention without having to send the calibration

22 data from the printer controller C to the LED printer head H.

23

24 Figure 4 shows a printing system according to a third embodiment of the

25 present invention performing a dither algorithm based on an error

26 diffusion method.

1

2 The error diffusion will be briefly described through an example where a

3 page is processed line by line from top to bottom and a line is processed

4 dot by dot from left to right.

5

6 In processing the first dot of the first line, its source value is shifted by an

7 error so as to render a resultant value. The resultant value of the first dot

8 of the first line is used to drive an LED. The error of the first dot of the

9 first line is divided and passed to the second dot of the first line and the

10 first and second dots of the second line. In processing the second dot of

11 the first line, its source value and the error from the first dot of the first

12 line are summed up and then shifted by an error so as to render a resultant

13 value. The resultant value of the second dot of the first line is used to

14 drive an LED. The error of the second dot of the first line is divided and

15 passed to the third dot of the first line and the first, second and third dots

16 of the second line. So are the rest dots of the first line except for the last

17 dot of the first line that does not have any dot to its right and lower right.

18

19 In processing the first dot of the second line, its source value and the

20 errors from the first and second dots of the first line are summed up and

21 then shifted by an error so as to render a resultant value. The resultant

22 value of the first dot of the second line is used to drive an LED. The

23 error of the first dot of the second line is divided and passed to the second

24 dot of the second line and the first and second dots of the third line. In

25 processing the second dot of the second line, its source value, the errors

26 from the first, second and third dots of the first line and the error from the

8

1   first dot of the second line are summed up and then shifted by an error so

2   as to render a resultant value.   The resultant value of the second dot of

3   the second line is used to drive an LED.   The error of the second dot of

4   the second line is divided and passed to the third dot of the second line

5   and the first, second and third dots of the third line.   So are the rest dots

6   of the second line except for the last dot of the second line that does not

7   have any dot to its right and lower right.

8

9   The remaining lines of the page are processed in an identical manner

10   except for the last line that does not have any line below it.

11

12   The error diffusion may be implemented in various other processes and

13   will not be further described in detail for being conventional.   It should

14   however be noted that the method and apparatus of according to the third

15   embodiment of the present invention can be performed together with any

16   error diffusion process.

17

18   Referring to Figure 4, the printer controller C includes a first adder 15, a

19   threshold block T connected with the first adder 15, a second adder 17

20   connected with the first adder 15, a multiplexer 16 connected with the

21   second adder 17, a calibration data memory 30 connected with the

22   multiplexer 16, an error memory 18 connected with the second adder 17

23   and a calculation block 22 connected with the error memory 18 on one

24   hand and connected with the first adder 15 on the other hand.

25

26   In operation, an original datum ("ORIGINAL_DATUM") of a dot

1 ("current dot") is sent to the first adder 15 from the data source S.

2

3 Errors of related previous dots are sent to the calculation block 22 from

4 the error memory 18. For example, the related previous dots are the

5 upper left, upper, upper right and left dots. The error of each related

6 previous dot is multiplied with a specific coefficient so as to render a

7 weighted error. The weighted errors are added up so as to render a

8 weighted error sum ("WES"). WES is sent to the first adder 15 from the

9 calculation block 22.

10

11 In the first adder 15, ORIGINAL_DATUM and WES are added up so as

12 to render a sum ("SUM").

13

14 SUM is sent to the threshold block T from the first adder 15. SUM is

15 compared with a threshold ("THRESHOLD"). An output ("OUTPUT")

16 is set to be 1 if SUM is greater than THRESHOLD and 0 if otherwise.

17 OUTPUT is sent to the LED printer head H. An LED ("current LED")

18 corresponding to the current dot is turned on or kept off based on

19 OUTPUT.

20

21 SUM is sent to the second adder 17 from the first adder 15. In the

22 second adder 17, an error of the current dot ("ERROR") is calculated. If

23 SUM is greater than THRESHOLD, the current LED is turned on and an

24 error ("LED_ERROR") related to the current LED occurs. In this case,

25 ERROR is set to be SUM minus OUTPUT minus a function of

26 LED_ERROR. If SUM is not greater than THRESHOLD, the current

1   LED is kept off and LED_ERROR does not occur.   In this case, ERROR

2   is set to be SUM.

3

4   ERROR is sent to the error memory 18 from the second adder 17.

5

6   Figure 5 shows a printing system according to a fourth embodiment of the

7   present invention using the calibration data to modify dithered data.   The

8   printer controller C includes a dither block 12, a first adder 15 connected

9   with the dither block 12, a latch 50 connected with the first adder 15, a

10   second adder 17 connected with the latch 50 on one hand and the first

11   adder 15 on the other hand, an error prediction block 32 connected with

12   the latch 50 and a calibration data memory 30 connected with the error

13   prediction block 32.

14

15   In operation, source data are sent to the dither block 12 from the data

16   source S.   In the dither block 12, the source data are dithered.   The

17   dithered data are sent to the first adder 15.   In the first adder 15, the

18   dithered datum of a dot ("current dot") and a sum of errors from previous

19   dots are added up so as to render a corrected value of the current dot.

20   The corrected value is sent to the latch 50 from the first adder 15.   In the

21   latch 50, the corrected value is divided into a portion consisting of high

22   order bits or most significant bits ("MSB") and a portion consisting of

23   low order bits or least significant bits ("LSB").

24

25   MSB represents the integer of the corrected value that will be realized by

26   means of an LED ("current LED").   MSB is sent to the LED printer

1 head H.   The current LED is turned on or kept off based on MSB.   The

2 error of the current LED thus occurs and must be compensated in some of

3 the following dots.   To this end, MSB is sent to the error prediction

4 block 32 from the latch 50.   The calibration value of the current LED is

5 sent to the error prediction block 32 from the calibration data memory 30.

6 In the error prediction block 32, an error ("MSB_ERROR") is estimated

7 by means of a formula or lookup table based on MSB and the calibration

8 value of the current LED.   Alternatively, the calibration value of a

9 neighboring LED may also be taken into consideration in the estimation

10 of MSB_ERROR.   MSB_ERROR is sent to the second adder 17 from

11 the error prediction block 32.

12

13 LSB represents the fractional or leftover portion of the corrected value

14 that is not realized by means of the current LED.   Hence, LSB is taken

15 as an error ("LSB_ERROR") and should be compensated in processing

16 some of the following dots.   LSB_ERROR is sent to the second adder 17

17 from the latch 50.

18

19 In the second adder 17, MSB_ERROR and LSB_ERROR are added up so

20 as to render a sum of errors.   The sum of errors is sent from the second

21 adder 17 to the first adder 15 for processing the next dot.

22

23 Figure 6 shows a printing system according to a fifth embodiment of the

24 present invention.   The fifth embodiment is identical to the fourth

25 embodiment except for installing the dither block 12 outside the printer

26 controller C.

1 The present invention has been described via detailed illustration of some

2 embodiments. Those skilled in the art can derive variations from the

3 embodiments without departing from the scope of the present invention.

4 Therefore, the embodiments shall not limit the scope of the present

5 invention defined in the claims.

6